¼ - 14 x ⅞" STITCH TEK 6" O/C

"SRC-02" METAL CLOSURE, REFER TO
SHEET __ FOR FASTENING INFORMATION

SR2 OUTSIDE CLOSURE STRIP
SET IN 1" x 3/16" BUTYL TAPE AT
TOP AND BOTTOM

BUTYL TAPE SEALANT

FIELD-FILL W/
COMPRESSIBLE INSULATION
(NOT BY IMP SUPPLIER)

"HE-__S" HIGH EAVE TRIM

POP RIVET 12" O/C

"WC-01" PANEL CLIP W/
(_) ¼ - 14 x _" TEK 3 W/O
WASHER AT PANEL JOINT

BUTYL SEALANT AT
VERTICAL JOINT

½"

1" x 3/16" BUTYL TAPE SEALANT
AT TOP AND BOTTOM

NOTE: BARE SRC-
PROVIDED FOR PROJECTS
WITH ROOF SLOPE ≤ 1:12
AND EAVE HEIGHT ≥ 20'.

SR-_ ROOF PANEL CLIP W/
(_) ¼ - 14 x 2" TEK 3 W/O WASHER, PER
CLIP, PER PANEL AT HIGH EAVE STRUT

BUTYL TAPE SEALANT (MARRY
TO VERTICAL SEALANT)

EAVE STRUT
(NOT BY IMP SUPPLIER)

NOTE: DO NOT OVER-DRIVE FASTENERS. IF THE
METAL AT THE EDGE OF THE PANEL IS DEFORMED
OUT OF PLANE, THE ADJACENT PANEL WILL BE
DIFFICULT TO ENGAGE AND WILL NOT SEAM.
AFTER SR CLIP HAS BEEN INSTALLED OVER MALE
LEG OF STANDING SEAM PANEL, PRE-CRIMP,
USING ½" HAND CRIMPING TOOL.

\#   HIGH EAVE

(SECTION VIEW)

DETAIL:
HIGH EAVE
APPLICATION:
SR ROOF, COMMERCIAL & INDUSTRIAL
AWIP DETAIL NUMBER:
SRR-ACI-HE-001

SHEET:
1 OF 1
DATE:
02/09/23
DRAWN BY:
MMF