



( ) 1/4 - 14 x TEK 3  
POLARFAST FASTENER,  
PER PANEL AT EACH  
SECONDARY SUPPORT

1/2" DIAMETER BEAD  
OF BUTYL SEALANT

"OC-03" OUTSIDE CORNER  
W/ POP RIVETS 12" O/C  
(SET TRIM IN 3/8" DIAMETER  
BEAD OF BUTYL SEALANT)

FIELD-CUT THERMAL BREAK

SECONDARY FRAMING  
(NOT BY IMP SUPPLIER)

GIRT CLIP  
(NOT BY IMP  
SUPPLIER)

"IC-01" INSIDE  
CORNER W/ #10 x 3/4"  
PPH @ 12" O/C  
(SET TRIM IN BUTYL  
SEALANT)

**NOTE: FIELD CUT STARTING PANEL  
AND ENDING PANEL AS REQUIRED  
AT CORNER TRANSITION.**

# # CORNER TRANSITION -FLAT OUTSIDE

(PLAN VIEW)

DETAIL:	CORNER TRANSITION - FLAT OUTSIDE		
	APPLICATION:	DATE:	SHEET:
	VERTICAL WALL, COLD-STORAGE	04/02/19	1
	AWIP DETAIL NUMBER:	DRAWN BY:	OF
	AVW-ACS-CT-002	MMF	1

929 ALDRIDGE ROAD  
VACAVILLE, CA 95688  
TEL: (707) 359-2280  
FAX: (707) 359-2286  
WWW.AWIPANELS.COM

