



() 1/4 - 14 x 3
POLARFAST FASTENER,
PER PANEL AT EACH
SECONDARY SUPPORT

ONE-PART EXPANDING
FOAM SEALANT (NOT BY
IMP SUPPLIER)

PEEL & STICK BITUMEN
MEMBRANE

"OC-03" OUTSIDE CORNER
W/ POP RIVETS 12" O/C
(SET TRIM IN BUTYL SEALANT)

FIELD-CUT THERMAL BREAK

SECONDARY FRAMING
(NOT BY IMP SUPPLIER)

GIRT CLIP
(NOT BY IMP
SUPPLIER)

"IC-01" INSIDE
CORNER W/ #10 x 3/4"
PPH @ 12" O/C
(SET TRIM IN BUTYL
SEALANT)

NOTE: FIELD CUT STARTING PANEL
AND ENDING PANEL AS REQUIRED
AT CORNER TRANSITION.

CORNER TRSN - FLAT OUTSIDE (FREEZER)

(PLAN VIEW)

DETAIL:	CORNER TRANSITION - FLAT OUTSIDE		
	DATE:	04/02/19	SHEET:
	DRAWN BY:	MMF	1 OF 1
APPLICATION:	VERTICAL WALL, COLD-STORAGE		
AWIP DETAIL NUMBER:	AWW-ACS-CT-006		

929 ALDRIDGE ROAD
VACAVILLE, CA 95688
TEL: (707) 359-2280
FAX: (707) 359-2286
WWW.AWIPANELS.COM

