

1/4 - 14 x 7/8" STITCH TEK 6" O/C

"HRC-__" METAL CLOSURE, REFER TO SHEET __ FOR FASTENING INFORMATION

HR_ OUTSIDE CLOSURE STRIP SET IN 1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

FIELD-FILL W/ COMPRESSIBLE INSULATION (NOT BY IMP SUPPLIER)

"HE-__" HIGH EAVE TRIM

POP RIVETS 12" O/C

"WC-01" PANEL CLIP W/ () 1/4 - 14 x _ TEK 3 FASTENERS W/O WASHER AT PANEL JOINT

1/2"

1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

NOTE: BARE HRC- PROVIDED FOR PROJECTS WITH ROOF SLOPE ≤ 1:12 AND EAVE HEIGHT ≥ 20'.

(3) 1/4 - 14 x _ TEK 3 FASTENERS W/ WASHER, PER PANEL (SPACED EVENLY)

BUTYL TAPE SEALANT

BUTYL TAPE SEALANT (MARRY TO VERTICAL SEALANT)

HIGH EAVE STRUT (NOT BY IMP SUPPLIER)

BUTYL SEALANT AT VERTICAL JOINT

HIGH EAVE

(SECTION VIEW)



DETAIL: HIGH EAVE	DATE:	02/08/23	SHEET:	1	OF	1
	APPLICATION:	HR ROOF, COMMERCIAL & INDUSTRIAL				
	AWIP DETAIL NUMBER:	HRR-ACH-HE-001				
929 ALDRIDGE ROAD VACAVILLE, CA 95688 TEL: (707) 359-2280 FAX: (707) 359-2286 WWW.AWIPANELS.COM						