


"OR-01" OUTSIDE RIDGE

FILL GAP CONTINUOUSLY WITH TWO-PART FOAMED-IN-PLACE URETHANE; FOR DRY, MILD CLIMATES COMPRESSIBLE INSULATION MAY BE USED (NOT BY IMP SUPPLIER)

1/4 - 14 x 7/8" STITCH TEK 6" O/C

NOTE: BARE HRC- PROVIDED FOR PROJECTS WITH ROOF SLOPE ≤ 1:12 AND EAVE HEIGHT ≥ 20'.



HR_ OUTSIDE CLOSURE STRIP SET IN 1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

SECONDARY FRAMING BY OTHERS (NOT BY IMP SUPPLIER)

"IR-01" INSIDE RIDGE W/ #10 x 3/4" PPH 12" O/C

"SW-01" SADDLE WASHER W/ 1/4 - 14 x _ TEK 3 W/ WASHER SPACED _ O/C (PILOT HOLE RECOMMENDED)

"HRC-_" METAL CLOSURE SET IN 1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM; REFER TO SHEET _ FOR FASTENING INFORMATION

1/2"

RIDGE APEX

(SECTION VIEW)



DETAIL: RIDGE APEX	DATE: 02/08/23	SHEET: 1 OF 1
	DRAWN BY: MMF	
APPLICATION: HR ROOF, COMMERCIAL & INDUSTRIAL		
AWIP DETAIL NUMBER: HRR-ACHRA-001		
929 ALDRIDGE ROAD VACAVILLE, CA 95688 TEL: (707) 359-2280 FAX: (707) 359-2286 WWW.AWIPANELS.COM		