

HR\_ INSIDE CLOSURE STRIP  
W/ 3/4" x 3/32" BUTYL TAPE  
SEALANT AT TOP & BOTTOM

3"

FIELD-FILL W/ COMPRESSIBLE  
INSULATION (NOT BY IMP SUPPLIER)

NOTE: FIELD-REMOVE FOAM  
& LINER AT CUTBACK.

1/4 - 14 x 7/8" STITCH  
TEKS 6" O/C

"LE-\_" LOW EAVE TRIM

POP RIVETS 12" O/C

"WC-01" PANEL CLIP W/  
(\_) 1/4 - 14 x \_ TEK 3 FASTENERS  
W/O WASHER AT PANEL JOINT

"SW-01" SADDLE WASHER W/  
1/4 - 14 x \_ TEK 3 W/ WASHER  
SPACED \_ O/C (PILOT HOLE  
RECOMMENDED)

BUTYL TAPE SEALANT

BUTYL TAPE SEALANT (MARRY  
TO VERTICAL SEALANT)

EAVE STRUT  
(NOT BY IMP SUPPLIER)

BUTYL SEALANT AT  
VERTICAL JOINT

#

# GUTTERLESS EAVE

(SECTION VIEW)



DETAIL:

## GUTTERLESS EAVE

929 ALDRIDGE ROAD  
VACAVILLE, CA 95688  
TEL: (707) 359-2280  
FAX: (707) 359-2286  
WWW.AWIPANELS.COM

**All Weather**  
Insulated Panels



APPLICATION:  
HR ROOF, COMMERCIAL & INDUSTRIAL  
AWIP DETAIL NUMBER:  
HRR-ACL-GE-001

DATE:  
02/08/23

DRAWN BY:  
MMF

SHEET:  
1 OF 1