

# DM40/DM44

AWIP ALLOWABLE LOAD TABLE

## DM40/DM44 Allowable Load Table (PSF) for AL-06 Tee with Clevis Ceiling

Panel Thickness	Panel Weight	Rod Spacing	Single Span Condition				
			10 psf	15 psf	20 psf	25 psf	30 psf
3"	2.41 psf	4'-0"	16'-5"	14'-2"	12'-7"	11'-5"	10'-5"
		4'-6"	16'-5"	14'-2"	12'-7"	11'-5"	10'-5"
		5'-0"	16'-5"	14'-2"	12'-7"	11'-5"	10'-5"
		5'-6"	16'-5"	14'-2"	12'-7"	11'-5"	10'-5"
		6'-0"	16'-5"	14'-2"	12'-7"	11'-5"	10'-5"
		6'-6"	16'-5"	14'-2"	12'-7"	10'-7"	8'-11"
		7'-0"	16'-5"	14'-2"	11'-2"	9'-1"	7'-8"
4"	2.62 psf	4'-0"	20'-0"	17'-4"	15'-5"	14'-0"	12'-11"
		4'-6"	20'-0"	17'-4"	15'-5"	14'-0"	12'-11"
		5'-0"	20'-0"	17'-4"	15'-5"	14'-0"	12'-11"
		5'-6"	20'-0"	17'-4"	15'-5"	14'-0"	12'-5"
		6'-0"	20'-0"	17'-4"	15'-1"	12'-4"	10'-5"
		6'-6"	20'-0"	16'-6"	12'-10"	10'-6"	8'-10"
		7'-0"	19'-10"	14'-2"	11'-0"	9'-0"	7'-8"
5"	2.82 psf	4'-0"	23'-3"	20'-2"	18'-1"	16'-6"	15'-2"
		4'-6"	23'-3"	20'-2"	18'-1"	16'-6"	15'-2"
		5'-0"	23'-3"	20'-2"	18'-1"	16'-6"	15'-0"
		5'-6"	23'-3"	20'-2"	17'-10"	14'-7"	12'-4"
		6'-0"	23'-3"	19'-2"	14'-11"	12'-3"	10'-4"
		6'-6"	22'-8"	16'-3"	12'-8"	10'-5"	8'-10"
		7'-0"	19'-6"	14'-0"	10'-11"	9'-0"	7'-7"
6"	2.98 psf	4'-0"	26'-3"	22'-11"	20'-6"	18'-9"	17'-4"
		4'-6"	26'-3"	22'-11"	20'-6"	18'-9"	17'-4"
		5'-0"	26'-3"	22'-11"	20'-6"	17'-7"	14'-11"
		5'-6"	26'-3"	22'-7"	17'-8"	14'-6"	12'-4"
		6'-0"	26'-3"	19'-0"	14'-10"	12'-2"	10'-4"
		6'-6"	22'-4"	16'-2"	12'-7"	10'-4"	8'-9"
		7'-0"	19'-3"	13'-11"	10'-10"	8'-11"	7'-7"
8"	3.31 psf	4'-0"	31'-9"	27'-9"	25'-0"	22'-10"	21'-2"
		4'-6"	31'-9"	27'-9"	25'-0"	21'-6"	18'-3"
		5'-0"	31'-9"	26'-11"	21'-1"	17'-5"	14'-9"
		5'-6"	30'-7"	22'-2"	17'-5"	14'-4"	12'-2"
		6'-0"	25'-8"	18'-7"	14'-7"	12'-0"	10'-3"
		6'-6"	21'-10"	15'-10"	12'-5"	10'-3"	8'-8"
		7'-0"	18'-9"	13'-8"	10'-8"	8'-10"	7'-6"

See notes on page 2.

1 (888) 970-AWIP (2947)  
awippanels.com  
sales@awippanels.com



**All Weather**  
Insulated Panels

Notes:

1. Allowable loads are live loads only. Self Weight of panels and aluminum tees have been taken into consideration.
2. Table is based on values derived from transverse load testing per ASTM E72 and strength of ceiling tee.
3. Panel properties are based on 26 gauge exterior and 26 gauge interior facings. Inquire about other gauges.
4. The Deflection Limit is L/180.
5. Safety Factor = 2.5 for buckling, 3.0 for core shear, 3.0 for hangar rod connection to tee.
6. The aluminum tee was designed in accordance with the 2015 Aluminum Design Manual.
7. Table applicable for ambient, controlled environment and cold storage applications. Inquire about hot rooms.
8. The strength of the hangar rods and its connection to the ceiling support structure must be engineered by a licensed engineering professional.
9. Collateral Loads must be directly supported by the building framing and not by the ceiling panels.
10. Consult your AWIP representative for project specific calculations.
11. Load tables are subject to change without notice - visit [www.awipanel.com](http://www.awipanel.com) for the latest information.



Scan For  
More Information

1 (888) 970-AWIP (2947)  
[awipanel.com](http://awipanel.com)  
[sales@awipanel.com](mailto:sales@awipanel.com)



**All Weather**  
Insulated Panels